Torstenson Glass Co.
3233 North Sheffield Avenue
Chicago, Illinois 60657-2210
773 525-0435 **Fax 773 525-0009**
w w w . t g l a s s . c o m
Flat glass distributors since 1889

QUOTATION REQUEST

FOR FIRE-RATED GLAZING MATERIALS

COMPANY _____ DATE _____

NAME _____ PROJECT NAME _____

ADDRESS _____ _____

CITY _____ DATE PRODUCT REQUIRED _____

STATE/ZIP _____ _____

PHONE _____ FAX _____

Impact Safety Products

- ☐ Firelite Plus Premium
- ☐ Firelite Plus Standard
- ☐ Firelite Plus Satin Etch
- ☐ Firelite NT Premium
- ☐ Firelite NT Standard
- ☐ Firelite NT Satin Etch

Non-Impact Safety

- ☐ Firelite Premium
- ☐ Firelite Standard
- ☐ Firelite Satin Etch

# of PCS.	Width	Height	RATING REQUIRED
	x		
	x		
	x		
	x		
	x		
	x		
	x		
	x		
	x		
	x		
	x		

# of PCS.	Width	Height	RATING REQUIRED
	x		
	x		
	x		
	x		
	x		
	x		
	x		
	x		
	x		
	x		
	x		

Glaze FireLite using closed cell polyvinyl chloride (PVC) glazing tape, pure silicone caulk, or DAP 33 glazing. If 90 Minute rated over 1,393 sq. in. of exposed glazing, use fire-rated glazing tape supplied by TGC or TGP.

Firelite and Firelite Plus are registered trademarks of Nippon Electric Glass Co.